



T H E S P E C I A L I S T S I N L A N D R O V E R S • U S A

Defender Mirror Head & Arm Assembly Instructions

1. Remove machine screw from bottom of mirror head. Cut the circular plastic bush so that it can be fitted around the pin on the mirror arm, with a pair of scissors.

Pic 1

NOTE: Do not attempt to remove the pin and ball from the mirror arm

2. Fit the cut bush around the pin on the mirror arm and assemble the mirror on to the arm.

3. When the assembly has been fitted to the vehicle, adjustment of the spring may be necessary. Remove the plastic cap at the bottom and adjust the nut underneath.

Pic 2



Pic 1



Pic 2

1 802 879-0032 or 1-800-403-7591 • Fax: (802) 879-9152
email@roversnorth.com • www.roversnorth.com

Rovers North, Inc. • 1319 VT Rt. 128 • Westford, Vermont • 05494-9601 USA



T H E S P E C I A L I S T S I N L A N D R O V E R S • U S A

Instructions Questionnaire

We rely on our customers to help us continually improve our instruction sheets. Please FAX or mail any comments, questions, or ideas for improvements you may have.

Send To: Rovers North
1319 Vermont Route 128
Westford, VT 05494

or Fax: 802-879-9152

Your Name: _____
Address: _____

Phone #: _____
Email Adrs: _____

Instruction part number (top right corner) or description of what instructions are: _____
Overall, how would you rate the quality of this set of instructions? (please circle one):

Poor		Fair		Good		Very Good		Excellent	
1	2	3	4	5	6	7	8	9	10

Ideas, Comments, or Corrections (please include specifics, such as page number, or step number):

THANK YOU!

1 802 879-0032 or (800) 403-7591 • Fax: (802) 879-9152
email@roversnorth.com • www.roversnorth.com
Rovers North, Inc. • 1319 VT Rt. 128 • Westford, Vermont • 05494-9601 USA