

ROVERS NORTH.com

Sales and Tech Support

	88 Basic		109 Regular		109 Station Wagon		90 Soft Top		110 Station Wagon	
DIMENSIONS AND WEIGHTS	British	Metric	British	Metric	British	Metric	British	Metric	British	Metric
Overall length	142.375"	3,62m	175"	4,44m	175"	4,44m	163"	3,884m	181"	4,599m
Overall width	66"	1,68m	66"	1,68m	66"	1,68m	70.5"	1,79m	70.5"	1,79m
Overall unladen height, hard top Overall unladen height, hood down, screen up	77.5" 68"	1,97m 1,73m	81"	2,06m	_	-	78"	1,981m _	82"	2,083m
Wheelbase	88"	2,23m	109"	2,77m	109"	2,77m	92.9"	2,360m	110"	2,794m
	51.5"	1,31m	51.5"	1,31m	51.5"	1,31m	58.5"	1,486m	58.5"	1,486
Turning circle	38'	11,6m	47"	14,3m	47"	14,3m	40.4"	12.3m	42"	12.8m
Unladen ground clearance under differentials, 5.00 x 16 tires	8"	203mm	_	_	_	-	_	_	_	_
Unladen ground clearance under differentials, 7.00×16 tires	8.75"	222mm	_	_	_	-	_	_	_	_
Unladen ground clearance under differentials, 2.50×16 tires	9.75"	248mm	9.75"	248m	9.75"	248m	9.75"	248m	9.75"	248m
Neight, running, with water, oil, 5 gallons fuel: Petrol models	2,953 lb	1,339 kg	3,301 lb	1,497 kg	3,752 lb	1,701 kg	3,560 lb	1,614.8 kg	4,848 lb	2,200 kg
Diesel models	3,097 lb	1,404 kg	3,471 lb	1,574 kg	3,922 lb	1,778 kg	-	-	_	-
Maximum approved payload, normal roads	1,410 lb	639 kg	2,263 lb	1,026 kg	1,835 lb	832 kg	2,435 lb	1,107 kg	2,371 lb	1,078 kg
Maximum drawbar pull - on road trailer w/brakes										
Petrol models	3,920 lb	1,775 kg	3,920 lb	1,775 kg	3,500 lb	1,600 kg	5,000 lb	2,275 kg	5,000 lb	2,275 kg
Diesel models	3,300 lb	1,497 kg	3,330 lb	1,497 kg	2,900 lb	1,315 kg	_	_	_	=
nternal body dimensions length (between cappings)	43"	1,09 m	72.75"	1,85 m	_	_	45"	1,144 m	_	=
width (between cappings)	56.8"	1,44m	56.8"	1,44 m	-	-	56.8"	144m	56.8"	144m
depth	19.5"	495m	19"	483 m	-	-	19.7"	500m	_	_
height of wheel arch	8.5"	216m	9"	219 m	_	-	9.2"	220m	9.2"	220m
width of floor (between wheel arch)	36.25"	921m	36.25"	921m	_	-	36.4"	925m	36.4"	925m
height, floor to roof (maximum)	48.5"	1,23m	48.5"	1,23m	-	-	47.4"	1,205m	46.3"	1,175m
height, floor to roof (maximum)	48.5"	1,23m	48.5"	1,23m	-	-	47.4"	1,205m	46.3"	1,17!

CAPACITIES	U.S. Unit	Liters	Туре	CAPACITIES	U.S. Unit	Liters	Туре
Engine oil w/filter, 4-cylinder	7.1 quarts	6.66	10w/40	Swivel pin housing oil (each)	1.2 pints	0,5	80w/90
Engine oil w/filter, 6-cylinder	6.5 quarts	6.1	10w/40	Swivel pin housing grease type	1.2 pinto	3.75 ml	0011/00
Engine oil w/filter, 8-cylinder	7.1 quarts	6.66	10w/40	Steering box, 4 + 6 cylinder	- 1 pint	0.5	80w/90
Air cleaner, 4-cylinder	1.8 pints	0.85	20/w	Power steering, 8 cylinder	3 quarts	2.9	Dextron IID
Main gearbox oil 4 + 6-cylinder	3 pints	1.5	80w/90	Fuel tank, except 109 Station Wagon	12 gallons	45	
Main gearbox 8-cylinder LT77S	2.3 quarts	2.2	Dextron IID	Fuel tank, 109 Station Wagon	19 gallons	73	
Main gearbox 8-cylinder R380	2.8 quarts	2.7	Texaco MTF94	Fuel tank, Defender 90	15.6 gallons	59	
Main gearbox 8-cylinder ZFauto	10 quarts	9.1	Dextron IID	Fuel tank, Defender 110	20.4 gallons	77.2	
Transfer box oil 4+ 6-cylinder	5.5 pints	2.5	80w/90	Cooling system, 4+ 6 cylinder	11 quarts	10.4	50/50
Transfer box 8-cylinder LT230	2.4 quarts	2.3	80w/90	Cooling system, 8 cylinder	13.6 quarts	12.8	Ethylene-
Rear differential } Rover type	1.8 quarts	1.75	80w/90				Glycol/
Front differential f hover type	1.8 quarts	1.75	80w/90				water mix
Rear differential ENV type	2.5 pints	1.2	80w/90				
Front differential J LINV type	3.1 pints	1.4	80w/90	Hydraulic front winch, supply tank	7.5 gallons	20	#68 Hydraulic
Rear differential Salisbury type	2 quarts	1.9	80w/90	Hydraulic front winch, gearbox	2.4 pints	1 1	#68 Hydraulic

